

Dahua Kamera IPC-HDBW2541E-S-0280B IP 5MP
polu-sferna anti-vandal IC kamera; WizSense
serija; Smart

Šifra: 122261
Kategorija proizvoda: Kamere IP
Proizvođač: DAHUA

Cena: **18.310,00** rsd.



IP polu-sferna anti-vandal IC kamera 5MP
1/2.7" CMOS, progresivno skeniranje (2960x1668 piksela)
Starlight+
Osetljivost 0.008Lux /F1.6 (kolor), 0.0008Lux /F1.6 (C/B), 0Lux (IC aktivan.)
IC LE diode dometa cca. 30m, Smart IC
Objektiv 2.8mm (Vidni ugao 111° horizontalno), 3.6mm opciono (92°)
Fiksni iris
Prava D/N funkcija (ICR)
BLC /HLC /WDR 120dB
3D DNR
ROI (do 4 zone)
Masking (do 4 zone)
AI analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region (uz detekciju ljudi i vozila) - SMD+
Inkorporiran mikrofon
Detekcija pokreta (do 4 zone)
Smart H.265+ /H.265 /Smart H.264+ /H.264 /H.264H /H.264B /MJPEG kompresija
Rezolucije 5M (2960 × 1668 i 2880 × 1620) /4M (2688 × 1520) /3M (2048 × 1536 i 2304 × 1296) /1080P /1.3M /720P /D1 /VGA /CIF
Dvostruki stream
Do 20fps u 2960 × 1668, do 25/30fps u 2688 × 1520 i nižim rezolucijama
RJ-45 (10/100Base-T) mrežni port
Protokoli IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
Interoperabilnost: ONVIF (Profile S/Profile G/Profile T), CGI, P2P, Milestone
Skladištenje: FTP, SFTP, MicroSD (do 256 GB), NAS
Potrebno napajanje 12VDC ili PoE (802.3af)
Potrošnja 6.1W, Wide voltage support ±30%
Dimenzije 81mm × 109.9 mm
Masa 0.34kg
Kućište od metala
IP67 i IK10 sertifikovana
Radna temp. -40°C~+60°C
CE-LVD: EN62368-1, CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU, FCC: 47 CFR FCC Part 15, Subpart B, UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07