

UPS Legrand DAKER DK + TowerRack,  
3000VA2700W, On Line Double Conversion,  
Sinusoidal, PFC, USB & RS232 port, 6 x IEC C13 &  
1 x IEC C19, bat

Šifra: 15601  
Kategorija proizvoda: UPS  
Proizvođač: LEGRAND

Cena: **117.733,00** rsd.



|  |                               |
|--|-------------------------------|
| UPS Technology:                        | Double Conversion Online      |
| Output Power Capacity:                 | 2700 W                        |
| Maximum Electrical Power Rating:       | 3000 VA                       |
| Nominal Output Voltage:                | 230 V                         |
| Voltage Phase:                         | Single                        |
| Status Notification Method:            | Alarm<br>LCD                  |
| Circuit Protection:                    | Over Temperature<br>Over Load |
| Status Alert Condition:                | Bypass<br>Fault               |
| Power Features:                        | Automatic Voltage Regulator   |
| Output Waveform:                       | Sinusoidal Wave               |
| Maximum Output Voltage:                | 230 V                         |
| Maximum Output Frequency:              | 60 Hz                         |
| Minimum Output Frequency:              | 50 Hz                         |
| Output Power Connectors Quantity:      | 6                             |
| Output Power Connectors Type:          | IEC-320 C13                   |
| Maximum Input Voltage:                 | 288 V                         |
| Minimum Input Voltage:                 | 160 V                         |
| Maximum Input Frequency:               | 60 Hz                         |
| Minimum Input Frequency:               | 50 Hz                         |
| Input Power Connectors Quantity:       | 1                             |
| Input Power Connectors Type:           | IEC-320 C19                   |
| Battery Location:                      | plug-in-module                |
| Battery Installed Quantity:            | 6                             |
| Maximum Peak Current Capacity:         | 9000 mAh                      |
| NetworkTransport Protocol:             | SNMP                          |
| Management Port Quantity:              | 1                             |
| Management Port Connector Type:        | RS-232 9-pin D-Sub            |
| Maximum Operating Ambient Temperature: | 40 °C                         |
| Maximum Operating Humidity:            | 80 %                          |
| Minimum Operating Ambient              |                               |

Temperature:

0 °C