

Cudy GS2008PS2 8-Port Layer 2 Managed Gigabit PoE+ Switch with 2 Gigabit SFP Slots, 120W

Šifra: 53126

Kategorija proizvoda: Switch uređaji

Proizvođač: CUDY



Cena: **14.420,00** rsd.

- 8 Gigabit POE Ports, 2 Gigabit Combo Ports, 1 Console Port
- Compatible with IEEE802.3at and IEEE802.3af
- Ethernet port supports 10/100/1000M adaptive
- Fanless design, Natural Cooling, Compatible with 1U Rack Mount
- Support PoE Power Management, PoE watchdog
- Lightning Protection Surge: General Mode 6KV, Differential Mode 4KV, ESD 15KV

AC INPUT: AC100-240V, 50/60Hz

Ethernet Port:

8 x 10/100/1000Mbps PoE Port

2 x 1000Mbps SFP Port

1 x RJ45 Console Port

Bandwidth: 20Gbps

Packet Forwarding rate: 14.88Mpps

DDR SDRAM: 128MB

Flash Memory: 16MB

Packet Buffer Memory: 4M

MAC Address: 8K

Jumbo frame: 9.6Kbytes

VLANs: 4096

Network Protocols:

IEEE 802.3: Ethernet MAC Protocol

IEEE 802.3i: 10BASE-T Ethernet

IEEE 802.3u: 100BASE-TX Fast Ethernet

IEEE 802.3ab: 1000BASE-T Gigabit Ethernet

IEEE 802.3z: 1000BASE-X Gigabit Ethernet (optical fiber)

IEEE 802.3ad: Standard method for performing link aggregation

IEEE 802.3x: Flow control

IEEE 802.1ab: LLDP/LLDP-MED (Link Layer Discovery Protocol)

IEEE 802.1p: LAN Layer QoS/CoS Protocol Traffic Prioritization (Multicast filtering function)

IEEE 802.1q: VLAN Bridge Operation

IEEE 802.1x: Client/Server Access Control and Authentication Protocol

IEEE 802.1d: STP

IEEE 802.1s: MSTP

IEEE 802.1w: RSTP

PoE protocol:

IEEE802.3af (15.4 W)

IEEE802.3at (30 W)

Network Media

10BASE-T: Cat3, 4, 5 or above UTP(=100 M)

100BASE-TX: Cat5 or above UTP(=100 M)
1000BASE-TX: Cat5 or above UTP(=100 M)

Multi-mode Fiber: 50/125, 62.5/125, 100/140um
Single-mode Fiber: 8/125, 8.7/125, 9/125, 10/125um

Operating temperature: -20~50°C
Storage temperature: -40~85°C
Operating Humidity: 10%~90%, No condensation
Storage Humidity: 5%~90%, No condensation
Working height: Up to 10,000 feet
Storage height: Up to 10,000 feet

Indicator: PWR, SYS, SW, PoE, Link/ACT